



U.S. General Services Administration

GovSales.gov Personal Property Portal Agency Implementation Guide

1800 F Street, NW
Washington, DC 20405-0002
www.gsa.gov

Executive Summary	3
1 Overview	3
1.1 Purpose.....	3
1.2 Contacts.....	3
2 Data elements.....	3
3 Process	3
4 Interface Options.....	4
4.1 XML Web Service	4
4.1.1 WSDL	4
4.1.2 Sample Transaction NewAssetRequest (used for update as well)	10
4.1.3 Sample Transaction DeleteAssetRequest	10
4.2 Flat / CSV file SFTP	11
4.2.1 Flat / CSV file schema	11

Executive Summary

The GovSales.gov Personal Property Portal Agency Implementation Guide is a tool to be used by sales agencies and their partners to facilitate agency integration to GovSales.gov. This guide specifies the connection options available, the type of transactions that can be submitted, and the data that can be submitted to the portal by sales agencies and their partners.

1 Overview

1.1 Purpose

The GovSales.gov Personal Property Portal Agency Implementation Guide specifies the steps necessary to submit sales agency asset data to the GovSales.gov Personal Property Portal.

1.2 Contacts

Name	Agency / Company	Email	Phone
Darlene Stickel, eFas Planning Office	GSA FAS Office of Personal Property Management	Darlene.stickel@gsa.gov	703.605.3404
Ben Murphy, Personal Property Portal Project Manager	GSA FAS Contractor	Benjamin.murphy@gsa.gov	703.605.5462
BP Perumal, Personal Property Portal Lead Architect	GSA FAS Contractor	bp.perumal@gsa.gov	703.605.9591

2 Data elements

The mandatory and option data elements that need to be provided to the portal are identified in the Web service WSDL or the Flat/CSV File schema.

3 Process

1. Select an interface option (web service or file over SFTP)
2. Request a test account with the govsales.gov test system
3. Submit test transactions
4. Verify test transactions
5. Request a production account with govsales.gov
6. Submit production transactions
7. Verify production transactions

4 Interface Options

4.1 XML Web Service

The GovSales.gov XML Web Service allows agencies or agency partners to submit web service requests to add, update, and delete asset data on the portal. The service is secured via SOAP header access tickets and is accessible over SSL (port 443).

4.1.1 WSDL

The GovSales.gov WSDL is an XML-based language that provides a model for describing the GovSales.gov web services.

```
<?xml version="1.0" encoding="UTF-8" ?>
<definitions name="HostWebServices" targetNamespace="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD"
  xmlns:tns="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/" xmlns="http://schemas.xmlsoap.org/wsdl/">
  <types>
    <schema elementFormDefault="qualified" targetNamespace="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD"
      xmlns:tns="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD" xmlns:wsdl="http://schemas.xmlsoap.org/wsdl/"
      xmlns="http://www.w3.org/2001/XMLSchema">
      <element name="NewAssetRequest">
        <complexType>
          <sequence>
            <xsd:element name="ITEM_ID">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="25"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
            <xsd:element name="COE_ID">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="3"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
            <xsd:element name="AGY_BUR">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="4"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
            <xsd:element name="FSC">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="4"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
            <xsd:element name="ITEM_NAME">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="80"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
            <xsd:element name="URL">
              <xsd:simpleType>
                <xsd:restriction base="xsd:string">
                  <xsd:maxLength value="256"/>
                </xsd:restriction>
              </xsd:simpleType>
            </xsd:element>
          </sequence>
        </complexType>
      </element>
    </schema>
  </types>
  <message name="NewAssetRequestMessage">
    <part name="parameters" type="tns:NewAssetRequest"/>
  </message>
  <message name="NewAssetResponseMessage">
    <part name="parameters" type="tns:NewAssetResponse"/>
  </message>
  <binding name="NewAssetBinding" type="tns:NewAssetPortType">
    <operation name="NewAsset" operationType="requestResponse">
      <input message="NewAssetRequestMessage"/>
      <output message="NewAssetResponseMessage"/>
    </operation>
  </binding>
</definitions>
```

```
</xsd:element>
<xsd:element name="QUANTITY">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="6"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="UNIT_MEASURE">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="30"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_NAME">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="36"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_ADDR1">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="36"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_ADDR2">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="36"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_CITY">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="30"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_STATE">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="2"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="LOC_ZIP">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="9"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="CUST_FNAME">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="16"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="CUST_LNAME">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="20"/>
</xsd:restriction>
</xsd:simpleType>
```

```
</xsd:element>
<xsd:element name="CUST_PHONE">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="10"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="CUST_PHONE_EXT">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="7"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="CUST_FAX">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="10"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="CUST_EMAIL">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="64"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="MAKE">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="20"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="MODEL">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="20"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="MANU_YEAR">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="4"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="COLOR">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="15"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="SIZE">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="10"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="MILEAGE">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="6"/>
</xsd:restriction>
</xsd:simpleType>
```

```

</xsd:element>
<xsd:element name="SALE_TYP_IND">
<xsd:simpleType>
<xsd:restriction base="xsd:string">
<xsd:maxLength value="10"/>
<xsd:enumeration value="IAUCTION"/>
<xsd:enumeration value="ISALE"/>
<xsd:enumeration value="LAUCTION"/>
<xsd:enumeration value="LSALE"/>
<xsd:enumeration value="SEALEDBID"/>
<xsd:enumeration value="SPOTBID"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="BID_DEPOSIT">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="12"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="BID_MINIMUM">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="12"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="BID_CURRENT">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="12"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="NUM_BIDS">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="3"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="SL_START_DATE">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="8"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="SL_START_TIME">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="4"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="SL_END_DATE">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="8"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
<xsd:element name="SL_END_TIME">
<xsd:simpleType>
<xsd:restriction base="xsd:integer">
<xsd:totalDigits value="4"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>

```

```

<xsd:element name="PHOTO_IND">
  <xsd:simpleType>
    <xsd:restriction base="xsd:string">
      <xsd:maxLength value="1"/>
    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
<xsd:element name="SPL_INSP_INFO">
  <xsd:simpleType>
    <xsd:restriction base="xsd:string">
      <xsd:maxLength value="256"/>
    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
<xsd:element name="DESCRIPTION">
  <xsd:simpleType>
    <xsd:restriction base="xsd:string">
      <xsd:maxLength value="4000"/>
    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
</sequence>
</complexType>
</element>
<element name="NewAssetResponse">
<complexType>
<sequence>
  <element name="mcpElapsed" type="xsd:integer" />
  <!-- Status of the transaction, 0 - successful,
       otherwise transaction was unsuccessful-->
  <xsd:element name="STATUS">
    <xsd:simpleType>
      <xsd:restriction base="xsd:string">
        <xsd:maxLength value="3"/>
      </xsd:restriction>
    </xsd:simpleType>
  </xsd:element>
  <xsd:element name="RESPONSE">
    <xsd:simpleType>
      <xsd:restriction base="xsd:string">
        <xsd:maxLength value="200"/>
      </xsd:restriction>
    </xsd:simpleType>
  </xsd:element>
</sequence>
</complexType>
</element>
<element name="DeleteAssetRequest">
<complexType>
<sequence>
  <xsd:element name="ITEM_ID">
    <xsd:simpleType>
      <xsd:restriction base="xsd:string">
        <xsd:maxLength value="25"/>
      </xsd:restriction>
    </xsd:simpleType>
  </xsd:element>
  <xsd:element name="COE_ID">
    <xsd:simpleType>
      <xsd:restriction base="xsd:string">
        <xsd:maxLength value="3"/>
      </xsd:restriction>
    </xsd:simpleType>
  </xsd:element>
</sequence>
</complexType>
</element>
<element name="DeleteAssetResponse">
<complexType>
<sequence>

```

```

<element name="mcpElapsed" type="xsd:integer" />
<!-- Status of the transaction, 0 - successful,
    otherwise transaction was unsuccessful-->
<xsd:element name="STATUS">
  <xsd:simpleType>
    <xsd:restriction base="xsd:string">
      <xsd:maxLength value="3"/>
    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
<xsd:element name="RESPONSE">
  <xsd:simpleType>
    <xsd:restriction base="xsd:string">
      <xsd:maxLength value="200"/>
    </xsd:restriction>
  </xsd:simpleType>
</xsd:element>
</sequence>
</complexType>
</element>
</schema>
</types>
<message name="NewAssetRequest">
  <part name="params" element="tns:NewAssetRequest" />
</message>
<message name="NewAssetResponse">
  <part name="params" element="tns:NewAssetResponse" />
</message>
<message name="DeleteAssetRequest">
  <part name="params" element="tns:DeleteAssetRequest" />
</message>
<message name="DeleteAssetResponse">
  <part name="params" element="tns:DeleteAssetResponse" />
</message>
<portType name="ProgramFASASSETLOADPort">
  <operation name="NewAsset">
    <input message="tns:NewAssetRequest" />
    <output message="tns:NewAssetResponse" />
  </operation>
  <operation name="DeleteAsset">
    <input message="tns:DeleteAssetRequest" />
    <output message="tns:DeleteAssetResponse" />
  </operation>
</portType>
<binding name="ProgramFASASSETLOADBinding" type="tns:ProgramFASASSETLOADPort">
  <soap:binding style="document" transport="http://schemas.xmlsoap.org/soap/http" />
  <operation name="NewAsset">
    <soap:operation soapAction="HostWebServices" />
    <input>
      <soap:body use="literal" />
    </input>
    <output>
      <soap:body use="literal" />
    </output>
  </operation>
  <operation name="DeleteAsset">
    <soap:operation soapAction="HostWebServices" />
    <input>
      <soap:body use="literal" />
    </input>
    <output>
      <soap:body use="literal" />
    </output>
  </operation>
</binding>
<service name="ProgramFASASSETLOADService">
  <documentation>Access Program FASASSETLOAD via MGSWeb</documentation>
  <port name="ProgramFASASSETLOADPort" binding="tns:ProgramFASASSETLOADBinding">
    <soap:address location="http://gsab0.fss.gsa.gov/HostWebServices/?ProgramFASASSETLOAD" />
  </port>
</service>

```

```
</service>
</definitions>
```

4.1.2 Sample Transaction NewAssetRequest (used for update as well)

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:SOAP-
ENC="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <SOAP-ENV:Body>
    <m:NewAssetRequest xmlns:m="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD">
      <m:ITEM_ID>807255726200731</m:ITEM_ID>
      <m:COE_ID>TRE</m:COE_ID>
      <m:AGY_BUR>4700</m:AGY_BUR>
      <m:FSC>2310</m:FSC>
      <m:ITEM_NAME>This is test item from webservice</m:ITEM_NAME>
      <m:URL></m:URL>
      <m:QUANTITY>14</m:QUANTITY>
      <m:UNIT_MEASURE>EACH</m:UNIT_MEASURE>
      <m:LOC_NAME>GSAXcess</m:LOC_NAME>
      <m:LOC_ADDR1>2100 CRYSTAL DRIVE</m:LOC_ADDR1>
      <m:LOC_ADDR2>RM 1010</m:LOC_ADDR2>
      <m:LOC_CITY>ARLINGTON</m:LOC_CITY>
      <m:LOC_STATE>VA</m:LOC_STATE>
      <m:LOC_ZIP>22202000</m:LOC_ZIP>
      <m:CUST_FNAME>BP</m:CUST_FNAME>
      <m:CUST_LNAME>PERUMAL</m:CUST_LNAME>
      <m:CUST_PHONE>7036059591</m:CUST_PHONE>
      <m:CUST_PHONE_EXT>454X</m:CUST_PHONE_EXT>
      <m:CUST_FAX>7036059595</m:CUST_FAX>
      <m:CUST_EMAIL>BP.PERUMAL@GSA.GOV</m:CUST_EMAIL>
      <m:MAKE>NISSAN</m:MAKE>
      <m:MODEL>ALTIMA</m:MODEL>
      <m:MANU_YEAR>2000</m:MANU_YEAR>
      <m:COLOR>PLATINUM</m:COLOR>
      <m:SIZE></m:SIZE>
      <m:MILEAGE>60250</m:MILEAGE>
      <m:SALE_TYP_IND>LACTION</m:SALE_TYP_IND>
      <m:BID_DEPOSIT>1009.2</m:BID_DEPOSIT>
      <m:BID_MINIMUM>200.20</m:BID_MINIMUM>
      <m:BID_CURRENT>5000</m:BID_CURRENT>
      <m:NUM_BIDS>1</m:NUM_BIDS>
      <m:SL_START_DATE>20071001</m:SL_START_DATE>
      <m:SL_START_TIME>1150</m:SL_START_TIME>
      <m:SL_END_DATE>20071130</m:SL_END_DATE>
      <m:SL_END_TIME>1010</m:SL_END_TIME>
      <m:PHOTO_IND></m:PHOTO_IND>
      <m:SPL_INSP_INFO>THIS IS SPECIAL ITEM POSTING THOUGH WEBSERVICE</m:SPL_INSP_INFO>
      <m:DESCRIPTION>TESTING</m:DESCRIPTION>
    </m:NewAssetRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

4.1.3 Sample Transaction DeleteAssetRequest

```
<SOAP-ENV:Envelope xmlns:SOAP-ENV="http://schemas.xmlsoap.org/soap/envelope/" xmlns:SOAP-
ENC="http://schemas.xmlsoap.org/soap/encoding/" xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <SOAP-ENV:Body>
    <m>DeleteAssetRequest xmlns:m="http://gsab0.fss.gsa.gov/Program/FASASSETLOAD">
      <m:ITEM_ID>807255726200731</m:ITEM_ID>
      <m:COE_ID>TRE</m:COE_ID>
      <m:DeleteAssetRequest>
    </m:DeleteAssetRequest>
  </SOAP-ENV:Body>
</SOAP-ENV:Envelope>
```

4.2 Flat / CSV file SFTP

The GovSales.gov Flat / CSV file SFTP interface allows agencies or agency partners to submit flat or CSV files to add, update, and delete asset data on the portal. The Report type field indicates the transaction type for that record in the file. The M/O refers to mandatory and optional data items.

4.2.1 Flat / CSV file schema

The following flat file schema can be used to create a flat or CSV file that can be SFTP'd to the GovSales.gov portal.

Data Element	M/O	Data Type	Data Format	Length	Position	Description
COE Item ID	M	X(25)	Alpha Numeric	25	1	A Unique item identifier used to reference a piece of property
COE ID	M	X(03)	Alpha Numeric	3	26	An Acronym that uniquely identifies a participating COE.
Report Type	M	X(10)	Alpha Numeric	10	29	Constant "NEW" for New Asset, "UPDATE" for Update Asset, "WITHDRAW" for Withdraw Asset, "DELETE" for Delete Asset, "UPDBID" for Update only Bid information
Agency Bureau	M	X(04)	Alpha Numeric	4	39	The Agency Bureau Code of the property owning Agency
Federal Supply Class	M	X(04)	Alpha Numeric	4	43	The Federal Supply Class of the Property
Item Name	M	X(80)	Alpha Numeric	80	47	The name of the piece of property for sale
URL	O	X(256)	Alpha Numeric	256	127	The URL that will be used to link the item on the FAS Portal to page hosted by the COE for that item. If a URL is not supplied a description page for the Item will be displayed with all of the relevant item information on it.
Quantity	M	9(06)	Number	6	383	The quantity of items for sale
Unit of Measure	M	X(30)	Alpha Numeric	30	389	The unit of measure associated with the Item Quantity (generally lot or each)
Property Location Name	M	X(36)	Alpha Numeric	36	419	Clear Text Name for Property Location
Property Location Address Line 1	M	X(36)	Alpha Numeric	36	455	Clear Text Address Line 1 for Property Location
Property Location Address Line 2	O	X(36)	Alpha Numeric	36	491	Clear Text Address Line 2 for Property Location
Property Location City	M	X(30)	Alpha Numeric	30	527	Clear Text City for Property Location
Property Location State	M	X(02)	Alpha Numeric	2	557	The State or Territory code for Property Location
Property Location ZIP Code	M	X(09)	Alpha Numeric	9	559	5 or 9 digit ZIP Code for property location in USA or 6 letters if Canadian or Blank if other foreign
Custodian First Name	M	X(16)	Alpha Numeric	16	568	Property Custodian First Name
Custodian Last Name	M	X(20)	Alpha Numeric	20	584	Property Custodian Last Name
Custodian Phone	M	9(10)	Number	10	604	Property Custodian Phone
Custodian Phone Extension	O	X(07)	Alpha Numeric	7	614	Property Custodian Phone Extension
Custodian Fax	O	9(10)	Number	10	621	Property Custodian Fax
Custodian Email Address	O	X(64)	Alpha Numeric	64	631	Property Custodian Email Address
Make	M/O	X(20)	Alpha Numeric	20	695	The manufacturer of the item.

						Mandatory if item is a vehicle
Model	M/O	X(20)	Alpha Numeric	20	715	The model of the item. Mandatory if item is a vehicle
Year	M/O	9(04)	Number	4	735	The four digit year the item was manufactured, e.g 2001. Mandatory if item is vehicle
Color	O	X(15)	Alpha Numeric	15	739	The color of the item
Size	O	X(10)	Alpha Numeric	10	754	The size of the item
Mileage	M/O	9(06)	Number	6	764	The mileage associated with the item. Mandatory if item is vehicle
Sale Type Indicator	M	X(10)	Alpha Numeric	10	770	A text description of the sale type. Valid values are: Internet Auction (IAUCTION), Internet Sale (ISALE), Live Auction (LAUCTION), Live Sale (LSALE), Sealed Bid (SEALEDBID), Spot Bid (SPOTBID), Fixed Price (FPRICE)
Deposit Amount	O	9(10)V99	Number	12	780	The amount of money a potential buyer must deposit in order to participate in the sale of the item
Minimum Bid	M	9(10)V99	Number	12	792	The minimum bid amount of the item
High Bid	O	9(10)V99	Number	12	804	The current high bid of the item
Number of Bids	O	9(03)	Number	3	816	The current number of bids placed on the item.
Sale Start Date	M	9(08)	Number	8	819	The date of the property sale is scheduled to start (e.g. 20061226 for 26th Dec 2006)
Sale Start Time	M	9(04)	Number	4	827	The time of the property sale is scheduled to start (e.g. 1310, for 1:10PM)
Sale End Date	M	9(08)	Number	8	831	The date of the property sale is scheduled to end (e.g. 20070103 for 3rd Jan 2007)
Sale End Time	M	9(04)	Number	4	839	The time of the property sale is scheduled to end (e.g. 0915, for 9:15AM)
Photo Availability Indicator	O	X(01)	Alpha Numeric	1	843	Used to indicate the photo availability at the COE hosted item description page. Y for photo available otherwise blank
Item Special Inspection Information	O	X(256)	Alpha Numeric	256	844	Special Inspection Information
FILLER		X(151)	Alpha Numeric	151	1100	Constant spaces
Description	M	X(4000)	Alpha Numeric	4000	1251	Complete description of the Asset
					5250	